

# ENSAC350

## Pneumatic opening bagging machine



**Paulo**

BALANÇAS - SCALES - BALANCES



### description

BAGGING MACHINE WITH WEIGHING HOODY AND PNEUMATIC OPENING.

### highlights

Suitable for weighing and bagging seeds and cereals up to 5 kg | Compact equipment to allow easy integration into the existing production structure | Dosing by motor-operated worm conveyor with variable speed drive | Dispensing cycle independent of the bagging operation | Pneumatic foot-operated opening.

### functions

additive bagging • Complete dispensing cycle programming • Automatic operation up to 999 cycles • Large and small flow • Automatic correction • Up to 10 product configurations.

### specifications

- Max weight per bag: 5 kg
- Maximum volume of the weighing hopper: 10 L
- Maximum volume of the feeding hopper: 50 L
- Production capacity: Up to 300 bags / hour, according to product characteristics
- Weighing accuracy: 1 g / 2 g
- Bagging accuracy: maximum error 1%
- Dimensions (L x H x D): 78x243x100 cm
- Weight: 250 kg

### controller

- Weight display: LED 6x14 mm
- Data display: 8x9 mm LED
- Indicators: zero, tare, stability, operation and status of inputs/outputs
- Keyboard: 20 function/alphanumeric keys
- 4 digital inputs
- 4 digital outputs
- 1xRS232; 1xRS485
- Protection: IP54
- Power: 230VAC / 50Hz (24VDC optional)
- Operating Temperature: 0°C +40°C
- Precision Class III (OIML)

### load cells

- 1x load cells 30 kg
- IP65 protection
- CE Approval / OIML R60

### options

Mouth/Small Bag Holder | Side table | feed hopper

